



Product Characteristic :-

Body	: High quality extruded/cast aluminum with treatment of corrosion protection and UV-proof powder coating
Diffuser	: Polycarbonate - Clear/Opal PMMA - Clear/Opal Tempered glass - Clear/Opal
Reflector	: Anodized high purity aluminum
Gasketing	: Thermostable silica gel to improve protection class
Fastener	: Stainless steel with high intensity and corrosion protection
Application	: Urban streets, parks, squares, garden, villas and etc.

Technical Data :-

Insulation Class	: Class I								
IP Rating	: IP65								
Lamping	: LED 35W - 42W : HQL Lamp 50W - 120W								
Color Temp.	: 3000K - 5000K								
Finishing Color	: <table><tr><td> WHITE, RAL 9010</td><td> GREY, RAL 9006</td><td> BLACK, RAL 9005</td><td> GREEN, RAL 6010</td></tr><tr><td> BLUE, RAL 5017</td><td> MAROON, RAL 3005</td><td> GOLD, RAL 1003</td><td></td></tr></table> : Other RAL colors are available upon request	 WHITE, RAL 9010	 GREY, RAL 9006	 BLACK, RAL 9005	 GREEN, RAL 6010	 BLUE, RAL 5017	 MAROON, RAL 3005	 GOLD, RAL 1003	
 WHITE, RAL 9010	 GREY, RAL 9006	 BLACK, RAL 9005	 GREEN, RAL 6010						
 BLUE, RAL 5017	 MAROON, RAL 3005	 GOLD, RAL 1003							

Dimension(mm) :

